Hazards and Preventions

ROADWAY SAFETY Awareness Program

Trainee Booklet



A Road Construction Industry Consortium Awareness Program

Numbers in Boxes in Index on adjacent page indicate the associated course module. For example:

Module 01 is Runovers and Backovers Module 02 is Operator Safetyand so on.....

Roadway Safety

Module Number

Contents

Introduction	1
07 Electrical Hazards	2
Fall Hazards 09	4
04 Flagger Safety	6
Health Hazards 11	8
05 Night Work	12
Noise Hazards 10	14
02 Operator Safety	16
Working Outdoors 12	18
01 Runovers and Backovers	21
Struck or Crushed 03	23
08 Sprains & Strains	24
Trenching	26
13 Emergencies	29
Safe Driving 14	30

Introduction



Building roads and highways can be dangerous. Each year about 7,500 highway construction workers get hurt or sick. More than 80 highway construction workers are killed on the job.

Our work doesn't have to be dangerous if:

- We are made aware of the hazards,
- We are given ways to avoid the hazards,
- We raise safety concerns with our supervisors.

Working together, we can make sure everyone goes home safe and healthy.

Electrical Hazards

What Are the Dangers of Electricity?

Contact with electricity can cause explosion, fire, and electrocution. Electricity can cause severe burns and death.

Equipment contacting a live electrical line can cause explosion, fire, or electrocution. Electricity can arc from the line to equipment.

Work around electricity only:

- when you are trained in all aspects of the job, and
- when you have a reason to be there.

How Do We Treat Above-Ground Utilities?

Minimum Safe Distances Power Lines

Distance

10

15

20

25

35

45

Voltage

50 kV or below

 $>50 - 200 \, kV$

>200 - 350 kV


> 350 - 500 kV

>500 - 750 kV

>750 - 1,000 kV

Use extreme caution and keep your distance when you must work around above ground utilities. The best practices are:

- Get the utility company to mark, flag, and shield line.
- Assume the line is live until it is tested. Have it de-energized and visibly grounded.



Post warning signs at ground level. Make anyone who must enter the area aware of the overhead lines. Here are two tips for operators:

- Mark a safe route for repeated travel.
- Slow down.

What If Contact Happens?

Do not touch equipment or a person in contact with electricity. Get the line de-energized. If you are in a vehicle that contacts electricity, stay in the vehicle and do not contact any metal. If you must exit, jump clear and slowly shuffle away. Keep your feet together to help prevent current from running through your body.

Can We Be Safe Around Buried Utilities?

Before digging, call the electrical, gas, and communications utilities. Review marked out areas. The mark out

may not be exact, so dig by hand within 3 feet of it.

When digging, look for:

- foreign debris in excavation,
- changes in mixed-up soil types,
- asphalt patches or depressions indicating previous digging, and
- concrete, plastic, or gravel.



Fall Hazards

What Causes Falls in Road Work?

Falls happen from one level to another or on the same level. Most falls in road construction are slips or trips on one level. Falls on walking/working surfaces include:

- Tripping over materials or debris.
- Falling on hills or embankments.
- Stepping in holes or walking on irregular ground.
- Stumbling while carrying loads that block vision.
- Slips or trips in muddy, wet, or icy conditions.

Less common falls from elevations include falls:

- From equipment. From bridges.
- From formwork. Into excavations.

How Do We Prevent Falls on Same Level?

Best protection practices include:

- Try to avoid muddy, wet, or icy surfaces.
- Use footwear with ankle support and soles that grip.
- Don't carry heavy loads. Use hauling equipment.
- Practice good housekeeping. Remove tools and materials when not in use.



- Fill in or mark hidden holes in the ground.
- Clear walking and working surfaces of tripping hazards.

Roadway Safety

• Include walking routes in the site safety plan.

A very important way to keep yourself from falling is to maintain good physical strength and conditioning.



How Do We Avoid Falls From Elevations?

Falls from elevations can be avoided

by many methods. Some good ways to avoid falls from elevations include:

- The employer should have a 100% fall protection program in place.
- Work should be pre-planned to provide for the use of personal fall arrest systems (PFAS) anchor points or guardrail systems.
- Erect guardrails around large excavations.
- Wear seatbelts or restraints for riding in cars, trucks, and personnel carriers.
- Use modular form erection to avoid work at heights on forms.
- Use 3-point contact.




Flagger Safety

What Is the Main Hazard of Flagging?

Motorists kill about 20 flaggers a year. Many more are injured. Flagging can be dangerous due to:

- High speed traffic.
- Angry or aggressive drivers.

After seeing a flagger, a motorist going 60 mph needs almost 400 feet to stop.



How Can We Protect Ourselves?

The best way to protect ourselves is to be visible and to wear protective clothing.

Wear high visibility clothing:


- Orange, yellow, or green vest.
- Only retro-reflective vests at night.

Wear other protective equipment:

- Hard hat.
- Long-sleeved shirt and pants.
- Appropriate clothes for expected weather.

Stay alert and out of harm's way. Follow these tips:

- Stand alone on the shoulder in clear view.
- Never stand in the open traffic lane.



- Stay alert, focused on work.
- Make sure your hand signals don't conflict with the traffic signals.

Roadway Safety

• Treat motorists with respect and courtesy. Don't pick fights or respond to anger. Notify law enforcement when motorists do not obey.






Health Hazards

How Do Health Hazards Harm Us?

Toxic substances can enter the body by three routes:

- breathing,
- swallowing, and
- absorption through the skin.



The effects of toxic substances in the body may be:

- short-term (acute) such as eye irritation or dizziness, or
- delayed (chronic) such as cancer or chronic lung disease.

How Harmful Is Silica?

Silica is in many construction dusts such as concrete and rock. Tasks that expose workers to large amounts of silica include sand blasting, rock drilling, and concrete drilling and grinding. Long-term exposure to silica leads to lung disease (silicosis). Long-term exposure also increases the risk of cancer. You can prevent exposure to silica by:

Roadway Safety


- reducing airborne dust through ventilation and wetting and
- using NIOSH-approved toxic dust respirators.

How Harmful Is Asphalt?

Asphalt fumes may cause eye and respiratory tract irritation. Hot asphalt can severely burn the skin.

To prevent exposure to asphalt:

- Work upwind whenever possible.
- Maintain a lower temperature to minimize fumes.
- Use ventilation on paving machines.
- Wear gloves and long-sleeved shirts to prevent skin contact.



A Road Construction Industry Consortium Awareness Program

How Harmful Is Wet Concrete?

Wet concrete can cause dermatitis and skin burns. Dermatitis can be either an irritation from chemicals in the concrete or an allergic reaction. The allergic type is very difficult to cure.

The best practices for preventing dermatitis and burns include:

- Wear long-sleeved or gauntlet gloves.
- Keep concrete out of your boots.
- Change your gloves and your boots if they become contaminated inside.
- Wash your hands in clean water with pH-neutral soap.
- Try using a neutralizing or buffering product.
- Protect all cuts with bandages.
- Wear eye protection.

How Harmful Is Lead?

Lead damages the nervous system and the reproductive system. Lead may be found in paints during bridge renovations. Lead dust and fume can be inhaled or ingested during sandblasting, welding, and cutting. Lead dust can be carried home on clothes and can poison your family.

Prevent lead poisoning by:

- Removing paint before cutting or welding.
- Using longhandled torches.
- Using local exhaust ventilation.
- Wearing the proper respirator.
- Washing face and hands before eating, smoking, or drinking.
- Showering and changing clothes before leaving work.
- Getting your blood level tested periodically.

Are There Other Health Hazards?

Other health hazards include common substances like solvents and carbon monoxide or special products such as sealants and paints. To avoid health hazards:

- Review the product Material Safety Data Sheets.
- Limit exposure as much as possible.
- Stay upwind of hazardous exposures.
- Make sure hazard controls like fans are working.
- MSDS
- Wear protective gear like respirators and skin coverings.
- Promptly report health complaints to your supervisor.

11







Night Work

What Are the Special Challenges of Night Work?

On the worksite, the challenges include:

- Poor visibility for motorists.
- Poor visibility for workers.
- Communication between shifts.
- Impaired or drowsy drivers.

Night work also causes physical and social disruptions, including:

- Sleep deprivation and disruption.
- Risk of injury from drowsiness.
- Impaired family or social relationships.

How Can We Protect Ourselves at Night?

Use special precautions at the work site for night work. Above all, you must increase visibility and know your surroundings.

To increase visibility:

- Wear retro-reflective clothing.
- Wear flashing lights on your body or clothing.
- Place retro-reflective tape on equipment.
- Use good work area lighting.



Know your surroundings:

- Know the vehicle and equipment paths.
- Know the assigned work areas.
- Know the safe paths to and from work.
- On foot, watch out for equipment.
- On equipment, watch out for workers.

Always provide clear signage. Space drums and cones closer together at night. For the best lighting, contrast the work lights from the warning lights.

Inspect the traffic control set up by test driving it to highlight problems and then inspecting it frequently.

How Can Our Health Habits Help?

Night work is not normal. You must compensate and your health habits can make a huge difference. On the work site, eat protein-rich foods and avoid sugars and fats. Drink plenty of water and avoid caffeine.

At home, make sleep a priority. Follow a pre-sleep routine and have a light snack before bedtime. Keep daylight out, even if you have to install black out drapes. Eat family meals together and plan daytime social activities. That way, you'll be ready for sleep when you come home from work.





STOP

Noise Hazards

Is Too Much Noise a Serious Problem?

If you are exposed to too much noise, you can lose your hearing — and you can lose your life.

On the job, too much noise can distract you. You may not hear warnings. Noise also damages the nerves in the inner ears. These nerves cannot be repaired.

After 15 to 20 years in the trade:

- You may suffer permanent hearing loss.
- You may hear constant ringing in your ears (tinnitus).

If you suffer hearing loss, you cannot hear well — especially when there is background noise. Hearing loss can adversely affect your family and personal life.

What Noise Sources Are Most Common?

There are many noise sources in road construction. Some of the most common include:

- heavy equipment,
- pile driving,
- pavement breakers,
- traffic.



Roadway Safety

Could Road Work Be Less Noisy?

Yes. There are efforts to make it quieter. Noise levels can be reduced by:

- Buy or rent quieter equipment.
- Keep equipment well maintained.
- Move noisy equipment away from workers.
- Put sound barriers around equipment.



How Do We Protect Our Hearing Now?

The best way to protect your hearing now is to wear personal protective equipment (PPE).

If you must shout to talk with someone 3 feet away, you need ear protection.



Use the PPE provided by your employer. Notify your employer if the PPE is not proper. Make



sure your PPE fits and is comfortable. Follow the manufacturer's instructions for use.

Get a hearing test about once a year so you'll know your hearing protection is working.

Operator Safety

How Can Operators Stay Safe?

Safe equipment operation includes these practices:

- Before starting vehicle, do a walk-around inspection.
- Test the back-up alarm and other safety devices.
- Locate and test controls.
- Know the equipment blind spots and the swing radius.
- Use equipment seatbelts.

When entering and exiting the vehicle:



- Climb with 3 points of contact to avoid falls.
- Look for other moving equipment or vehicles.
- Wipe up grease and fluid on equipment walking/working surfaces.

What Are Other Safety Measures?

Stay alert and aware of the hazards. Report all repair needs to your supervisor. Always lock out and tag out equipment that cannot be operated. For general safety:

- Use personal protective equipment (PPE) supplied and required by your employer.
- Never use cell phones, AM/FM radios, CD players, or other distractions while operating equipment.

Roadway Safety

- Safely secure equipment before using employerprovided hand-held cell phones or walkie-talkies.
- Secure unattended equipment.
- Lock-out/tag-out before repair or maintenance. Set the parking brake and chock the wheels.

How Can We Be Safe in the Work Zone?


The operator has special responsibilities. Know the job:

- Know the work zone and your position in it.
- Know the internal traffic control plan.
- Use designated equipment routes and areas.
- Identify rollover hazards.
- If you must move cones or barricades, return them to their original positions as soon as possible.

How Can We Protect Other Workers?

Keep other workers in mind:

- Know the locations of other workers around you.
- Set up a means of communication with them.
- Never allow them to ride on equipment.
- Provide barriers between workers and equipment, when possible.
- Avoid excess speed and dangers caused by hills, obstacles, and curves.





A Road Construction Industry Consortium Awareness Program

Working Outdoors

What Is Our Risk from Sun Exposure?

Skin cancer is the most serious risk. You are at greater risk if you have lighter skin with freckles or moles. Work at higher elevations and work

around reflective material like concrete or water also increase your risk. You can protect yourself with:

- A long-sleeved shirt and pants in neutral colors.
- A broad-brimmed hat with a neck flap.
- Safety glasses with tinted polarizing lenses.
- SPF 15-25 sun block applied 30 minutes before work and reapplied every 2 to 3 hours.
- Frequent checks of skin for early signs of cancer and seeing a dermatologist for check-ups.

How Are Plants and Animals Hazardous?

Plants and animals can cause rashes, illness, and even death. Outdoor work can expose you to animal bites, such as from dogs or snakes, and to plants like poison ivy and poison oak. To prevent problems:

18

- Steer clear of any animals.
- · Learn to recognize, avoid poisonous plants.
- Wear long-sleeved shirts and pants.
- Check for tick bites each day.
- Get prompt treatment.



Roadway Safety

What Are the Hazards of Hot Weather?

Hot weather can lead to heat stress, heat exhaustion, or heat stroke. Heat illness can be caused by a combination of:

- Heat exposure.
- High humidity.
- Non-breathing synthetic clothing.
- Not drinking enough fluids to replace sweat.
- Hard work, body heat, not being "acclimatized."

Heat stress can lead to heat rash, cramps, exhaustion, and stroke. Heat stress may be more likely if you are overweight and not fit. Alcohol greatly increases the risk.

What Is Heat Exhaustion?

Heat exhaustion is a dangerous illness. Symptoms include:

- Extreme weakness or fatigue.
- Dizziness, confusion.
- Nausea.
- Clammy moist skin
- Pale or flushed complexion.
- Slightly elevated body temperature.
 Caution
 Less hazardous



Heat exhaustion treatment includes resting in a cool, shaded place and drinking plenty of water.



- 30%
 - Humidity Temperature

Danger

80°

19

What Is Heat Stroke?

Heat stroke can cause hallucinations and death. Symptoms are red or spotted hot dry skin, no sweat, chills, high body temperature, mental confusion, and slurred speech. Call 911. Remove the victim to a cool shaded area. Soak clothes with water. Fan the body and apply ice to bring down temperature.



To protect yourself:

- Wear light-colored clothing.
- Gradually build up to heavy work.
- Schedule heavy work during coolest parts of day.
- Take more breaks in extreme heat and humidity.
- Drink lots of water, at least 2 to 3 quarts a day.

What Are the Hazards of Cold Weather?

Cold stress can lead to hypothermia and frostbite. Cold stress is caused by a combination of cold or cool temperatures (50° F or less), wet weather and/or conditions, high winds (40+ MPH), and inadequate clothing.

- Wear warm layers of correct clothing.
- Wear a head cover, warm gloves, and wool socks.

20

- Breaks in warm areas and hot liquids.
- Keep in good physical shape.
- Keep dry.



Runovers and Backovers

Can We Be Safe Near Equipment and Traffic?

Being struck is the biggest danger in road work. Workers on foot must remain alert at all times. Check

surroundings often. Listen for warnings. Keep a safe distance from traffic. Stay behind barriers where possible. Look out for each other. Warn coworkers.

What Other Precautions Do We Need?



- Employers must provide proper personal protective equipment (PPE). Workers must wear it:
- Proper class of safety vest at all times in the work zone.
- High-visibility clothing and headgear.

What About Construction Equipment?

Treat equipment and vehicles with caution:

- Stay out of "blind spots."
- Communicate with operators by radio and/or eye contact.





- Don't approach until you communicate with the operator and he/she acknowledges you.
- Stay outside a "safety circle" around equipment. If you can't see the operator, he/she can't see you.



- Stay clear of vehicles. Know the traffic control plan.
- Use spotters when you must work with your back to equipment or traffic.

How Can We Be Safe When Placing TCDs?

Simple precautions make placement of TCDs (Traffic Control Devices) safer. Workers should:

- Wear a Class III vest to be easily seen.
- Place, relocate, or remove TCDs when traffic flow is light.
- When possible, work from platform on vehicle.
- Use seat, seatbelt, fall restraint, or guardrail and a handhold when guardrail must be removed.
- Stay in constant communication with driver.
- Use shadow vehicle to warn drivers.



Struck or Crushed

How Are Road Workers Struck or Crushed?

Tools and materials are two major hazards. To avoid being struck by tools:

- Use point of operation guarding on portable hand tools.
- Use a chain saw safety program.
- Use Personal Protective Equipment (PPE).

To avoid being struck or crushed by materials:

- Keep out of lifting areas, from beneath loads.
- Use safe methods for rigging, hoisting, and setting steel plates, jersey barriers, manhole frames and covers.
- Use PPE hard hats, footwear, eye protection.

Trees and equipment maintenance are also hazards. To avoid being struck by trees, restrict worker access during felling, trimming, loading. Use protective structures on equipment. Use safe hoisting, rigging for logs and limbs.

To avoid being struck by equipment parts, do lockout/tagout and hazardous energy control during maintenance, repair, cleaning, and inspection.



Sprains & Strains

What Injuries Are Most Common?

About 43% of lost work day injuries in roadway construction are sprains and strains. Common injuries include:

- Hand and wrist problems.
- Back injuries.
- Sprains, strains, and overexertion.

What Causes These Injuries?

Think of the most difficult parts of your job. These injuries may be caused by some of these tasks, like:



- Working in awkward postures, such as raking asphalt.
- Handling heavy materials, like in concrete formwork.
- Repetitive work, like rebar tying.
- Using vibrating tools like a pavement breaker.
- Whole body vibration for operators.



How Can We Avoid Sprains and Strains?

Think of ways to do the job differently. We can make our work easier:

- Minimize manual materials handling with dollies, hoists, and other equipment.
- Better job planning (deliver materials where they're used).
- Store materials for easy access.



• Use tools that are comfortable and easy to handle.

Personal Protective Equipment (PPE) and breaks can help:

- Wear PPE, like kneepads and shoulder pads.
- Take breaks when possible, rotate difficult and easier tasks.

What Can You Do to Prevent Injuries?

Do at least some of these measures:

• Plan and maintain a clear, level walking path.



walking path.Don't lift too much by yourself.



- Get help.Use proper lifting technique. Lift
- with your legs, not your back when possible.
- Do stretching exercises before work.
- Keep fit.



Trenching

Why Are Trenches Dangerous?


A trench is an excavation deeper than it is wide. Trenches can kill:

- Workers can be buried alive.
- Cave-ins can result from stresses in walls, nearby moving vehicles and equipment, or spoil piles.
- Water can collect in the bottom.
- Flammable and toxic gases can build up.
- Gas from nearby sewer or gas lines can seep into the trench.

Before digging:

- Call electrical, gas, and communications utilities.
- Use extreme caution with equipment.

Trenches more than 4' deep meet OSHA's definition of a confined space.



Roadway Safety

How Do We Prevent Cave-Ins?

Protective systems are the methods or structures that *protect* us from cave-ins. A *protective system* must suit the soil type, the depth of the excavation, and other site conditions. It must resist without failure all loads intended or reasonably expected to be put on it.

The primary types of protective systems are:


 Sloping — soil angled to increase stability






 Benching steps in the trench wall.

• Shoring — a support system made of posts, wales, struts, and sheeting or hydraulic shoring.



 Trench Shielding — a protective frame or box to protect rescue workers after a cave-in


Trenches 5 feet or deeper require support unless they are in stable rock.



What Else Does Trenching Require?

The employer must designate a 'competent person' in every trench job. The 'competent person' must inspect:

- At least daily and at the beginning of each shift.
- After precipitation, a thaw, and other events that could increase hazard.
- For disturbed ground, water, toxics, and other hazards.
- If walls sag or crack or if the bottom bulges.
- To keep spoil and equipment at least 2 feet from trench edge.
- If there are nearby vibration sources such as railroads or piledriving.
- That no worker is more than 25 feet from an exit ladder.



The 'competent person' should stop work if a hazard exists.

Competent person means "one who is capable of identifying existing and predictable hazards in the surroundings or working conditions ... and who has authorization to take prompt corrective measures to eliminate them."

Roadway Safety

Emergencies

What Emergencies Are Most Common?

There are many different possible emergencies. The most common emergencies are:

- A worker is killed or seriously injured.
- Contact with gas line or electrical line.
- Trench collapse.
- Traffic entering the work zone.



• Toxic chemical spill.

What Should We Do in an Emergency?

The employer must have a plan. Emergency steps are:

- Call 911 and get medical help as soon as possible.
- Contact on-site first aid/CPR.
- Shut off any equipment and evacuate area if there are potential toxic exposures or explosions.
- On-site emergency coordinator contacts fire department/emergency response team.
- On-site emergency coordinator contacts utility company, if applicable.

After an emergency, ask for counseling if you have been affected by a tragedy or near miss.

How Do We Prepare for an Emergency?

You must know your employer's plan. Emergency planning includes:

- Warning system and signal to alert workers for evacuation.
- Everyone must know where the emergency phone numbers are posted for hospital, fire fighters, utilities, etc.





- Everyone must know who the emergency coordinator is and who is trained in first aid/CPR.
- Everyone must be trained in the emergency plan and participate in regular drills.

Safe Driving

How Do We Drive Safely?

Each year many road construction workers die driving to or from work or between work sites. Like other motorists, you should follow safe driving tips:

- Check vehicle to make sure all safety devices (brakes, turn signals, headlights, tail lights, horn) are operable and effective.
- Adjust mirrors to give yourself optimal view.
- Always use seat belt.

Roadway Safety

- Avoid distractions don't eat, drink, or talk on cell phone. Pull over or ask passenger to make calls.
- Don't drive if you are drowsy or drunk. Some prescription and OTC drugs also affect driving.
- Don't speed. Go at or below posted limit slower in bad conditions.
- Buy vehicles with front and side air bags and ABS brake system.
- Drive with headlights on even in daytime.
- Drive defensively.
- Avoid aggressive driving, e.g. quick lane changes, and tailgating.
- Map out a route ahead of time if you are unfamiliar with where you are headed.
- Never let anyone ride in the bed of your pick-up truckposted for hospital, fire fighters, utilities, etc.



What Should Road Workers Remember?

Road workers face special driving hazards. Construction vehicle operators should:

• Keep cab clean to prevent slippery pedals and debris under brake pedal.

- Keep all window glass clean and in good repair to prevent distortion.
- Make sure all cargo is secured to prevent it from striking the cab.
- Be careful changing lanes. Change only when it is necessary.
- Keep a safe distance from vehicles in front of you.



- Back up as little as possible.
- Be especially cautious at rail crossings.

What Should Road Workers Remember After a Night Shift?

Night work is not normal. You must compensate. Your health habits can make a huge difference.

On the work site, eat protein-rich foods and avoid sugars and fats. Drink plenty of water and avoid caffeine.



Only if you <u>need</u> it, drink coffee or another caffeinated beverage *after work* to help get you home.

Engineers (IUOE), the American Road & Transportation Builders Association (ARTBA), and the National Asphalt Pavement Association (NAPA). It any member of the consortium organizations imply endorsement by the U.S. Government. No statement made in this booklet should be construed to convey an impression that "safe and healthful workplace" as mandated by the Occupational Safety and Health Act. Produced for the consortium by FOF Communications All rights reserved. This material was produced under grant number 46C1-HT21 from the Occupational Safety & Health Administration, U.S. Department of Labor to a consortium of the Laborers' Health & Safety Fund of North America (LHSFNA), the International Union of Operating does not necessarily reflect the views or policies of the U.S. Department of Labor, nor does mention of trade names, ©2002, 2003, 2004, 2005, 2006 Laborers Health & Safety its affiliates, or employees have assumed any part of the employer's exclusive legal responsibility for providing a Fund of North America, Washington, DC commercial products, or